

**PRECISION MEETS
PRODUCTIVITY HERE.**



SB40

M40

KINTA DIESEL 4WD TRACTOR

SB40 | M40

**Effortlessly Handle Any Task with The New 40HP Series Tractor:
The Ultimate Companion for Your Plantation.**

New styling and flexible body weight options to best suit your daily operations to maximise your productivity and profit.



A true partner in your tractor ownership and maintenance solution.



www.allplanters.com.my

Specifications

	SB 40	
Engine	Drive type	4WD
	Engine model	C490BT
	Number cylinders/cc	4 / 2540
	Engine power kW (hp)	29.40 (40)
	@ rated speed (rpm)	2400
	Max torque @ 1700 rpm	142 Nm
	Compression ratio	18.4:1
PTO	PTO kW (hp)	25 (34)
	Type	Two Speed live PTO
	Shaft speeds	540/ 760 rev/min 1000/ 2000 rev/min
	Shaft diameter	35 mm
	Configuration	6 spline
Clutch	Type	Single plate, dry, disc spring compress, dual stage (imported JpV Clutch)
Transmission	Type	Shuttle mesh with creeper gear
	Speeds	12 F x 12 R
	Normal speed range	9.03 -- 31.37 km/h
	Creeper speed range	2.10 -- 7.32 km/h
Hydraulic System	Functions	Draft position & Floating control
	Standard oil flow	22 lit / min
	Nominal pressure	16 MPA ± 0.5
Three Point Linkage	Type	2 cat. ISO
	Max. Lift capacity	1030 kg
Brakes and Steering	Brake type	Oil Immersed mechanically operated Together or Independently
	Steering type	Hydrostatic
Tyre Matrix	Rear tyres	12.4 X 28
	Front tyres	8.3 X 20
Dimensions/ Weight	Width (mm)	1750
	Height (mm)	2130
	Length (mm)	3780
	Wheel base (mm)	1924
	Weight with ballast (kg)	2150
Capacities	Fuel (litres)	38

Sole distributor:

All-Planters Sdn. Bhd.
no.17, Jalan Desa 2, Taman Desa,
86000, Kluang, Johor.
Malaysia.
Tel : +607 777 1017
Fax : +607 773 8778

Email : enquiry@allplanters.com.my

Every effort has been made to ensure that the information contained is accurate and current as possible.

